

ISU 2X64

Dual Port ISDN Service Unit

Front View



Rear View



Physical Interfaces

■ Integrated Ports

- One RJ-45 for ISDN BRI U Network Interface
- Two DB-25: each RS-530/EIA-232 Interfaces
- V.35 Interfaces available with V.35 adapter cables
- Two EIA-366 DTE Dial Interface

Performance and Design Considerations

■ Network Interface

- Physical Interface: RJ-45
- ISDN Switch Types
 - National ISDN-1
 - Lucent 5ESS
 - Nortel DMS-100
 - NEC
- Dialing Selections
 - Manual or Automatic Stored Number Dialing
 - DTR Assertion
 - In-Band DTE Dialing: V.25 bis, AT Commands
 - Dial Interface: EIA-366

■ DTE Interface Data Rates

- Using Single DTE Interface
 - 1200 bps to 115.2 kbps asynchronous
 - 2400 bps to 128 kbps synchronous
- Using Dual DTE Interfaces
 - 1200 bps to 57.6 kbps asynchronous
 - 2400 bps to 64 kbps synchronous

Physical Specifications

- Chassis: Stand Alone
- Dimensions: 2.25" H, 7.5" W, 10" D
- Weight: 3.6 lbs
- Operating Temperature: 32°F to 122°F (0°C to 50°C)
- Mean Time Between Failure (MTBF): 753,109 Hrs

Power Specifications

- AC Power: 115 VAC
- Power Consumption: 8 W, 258 BTU

Agency Approvals

- FCC part 15 Class B, FCC Part 68
- UL, CUL

Warranty

- 5 Year (Repair & Return)
- www.ADTRAN.com/Warranty

Product Includes

- All ISU units ship with the following:
 - One 7 ft. telephone cable
 - User Manual

For additional product information including data sheets, manuals, installation guides, etc. please visit:
www.ADTRAN.com/ISU

For network design assistance or general inquires please visit:
www.ADTRAN.com/DesignAssistance

Ordering Information

ISU 2X64	Part Number
ISU 2X64	1200051L1

DISCLAIMER

ADTRAN provides the foregoing application description solely for the reader's consideration and study, and without any representation or suggestion that the foregoing application is or may be free from claims of third parties for infringement of intellectual property rights, including but not limited to, direct and contributory infringement as well as for active inducement to infringe. In addition, the reader's attention is drawn to the following disclaimer with regard to the reader's use of the foregoing material in products and/or systems. That is:

ADTRAN SPECIFICALLY DISCLAIMS ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL ADTRAN BE LIABLE FOR ANY LOSS OR DAMAGE, AND FOR PERSONAL INJURY, INCLUDING BUT NOT LIMITED TO, COMPENSATORY, SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR OTHER DAMAGES